

|                                       |                       |
|---------------------------------------|-----------------------|
| Part Number                           | VN-HC2x2-03538-OP-xxx |
| Operating Frequency ( MHz )           | 350/380-3800          |
| Impedance ( Ohm )                     | 50                    |
| VSWR                                  | 1.25                  |
| Coupling (dB)                         | 3                     |
| Insertion Loss (dB)                   | ±1.0                  |
| Isolation (dB)                        | 23                    |
| IM3 (dBc @ 2×43dBm)@xxx               | -150/-153/-161/-165   |
| Application                           | Indoor & Outdoor      |
| Degree of Protection                  | IP65                  |
| Operating Temperature ( °C )          | -40 ~ + 80            |
| Interface                             | 4.3-10 Female         |
| Handling Power (Watt, max)            | 500                   |
| Peak Power (Watt, max)                | 1500                  |
| Dimension (mm)(L×W×H, excl connector) | 184.8X44X43           |
| Packing Dimensions (mm,L×W×H)         | 250X105X50            |
| Packing Carton Size (mm,L×W×H)        | 565X260X120           |
| Net Weight (g)                        | 1105±5%               |
| ROHS Compliance                       | Yes                   |
| Revision                              | R1                    |
| Date                                  | 25-Oct-2022           |

